



Harmonia

Enhancing Data Placement and Migration in Hybrid Storage Systems via Multi-Agent Reinforcement Learning

[Rakesh Nadig](#), Vamanan Arulchelvan, Rahul Bera, Taha Shahroodi,
Gagandeep Singh, Andreas Kosmas Kakolyris, İsmail Emir Yüksel,
Mohammad Sadrosadati, Jisung Park and Onur Mutlu

ICS 2026

SAFARI
ETH zürich

AMD

POSTECH

Talk Outline

Background and Motivation

HSS Data Management using Reinforcement Learning

Harmonia: Overview

Evaluation and Key Results

Conclusion

Talk Outline

Background and Motivation

HSS Data Management using Reinforcement Learning

Harmonia

Evaluation and Key Results

Conclusion


Hybrid Storage System (HSS)

Unified Virtual Address Space

High-End Devices



Mid-Range Devices



Low-End Devices



Higher performance,
higher cost/GB

Lower cost/GB,
lower performance

Hybrid Storage System (HSS)

An HSS *combines multiple storage devices* with different *performance and cost characteristics* under a *single unified address space*

Hybrid Storage System (HSS)



AI/ML Infrastructure



High-Performance Computing (HPC) Clusters

Edge & Embedded Systems



Enterprise Storage Systems



Factors Affecting HSS Performance

HSS performance depends on two key factors:

**Where is the
data placed?**



Data Placement

*Select the best-fit device for
each new write*

**When and where to
migrate data?**



Data Migration

*Reorganize data across
devices over time*

Factors Affecting HSS Performance

HSS performance depends on two key factors:

**Where is the
data placed?**



Data Placement

*Select the best-fit device for
each new write*

**When and where to
migrate data?**




Data Migration

*Reorganize data across
devices over time*


Data Placement

Choose the best-suited HSS storage device for each incoming write or allocation request



Data Placement

Choosing the **best-suitable HSS storage device** for each incoming write or allocation request




Data Placement: Key Requirements



Need to operate with *low latency* on the *critical path* of *I/O handling*



Make accurate, yet *low-overhead* decisions



Adapt to changes in workload and system conditions



Factors Affecting HSS Performance

HSS performance depends on two key factors:

Where is the
data placed?



Data Placement

*Select the best-fit device for
each new write*

When and where to
migrate data?




Data Migration

*Reorganize data across
devices over time*


Data Migration

Reorganize data across HSS devices (e.g., prefetch hot data to the high-end devices and **evict cold data** to the low-end devices) to sustain high HSS performance




Data Migration

Reorganize data across HSS devices (e.g., prefetch hot data to the faster devices and evict cold data to the slower devices) to sustain high HSS performance



Data Migration


Reorganize data across HSS devices (e.g., prefetch hot data to the faster devices and evict cold data to the slower devices) to sustain high HSS performance



Data Migration: Key Requirements



Need to operate in the background,
off the critical path of I/O handling



Minimize interference
with foreground I/O operations



Perform *timely migrations* to *adapt*
to *workload and system changes*

Key Limitations of Prior Techniques

Prior HSS techniques *do not optimize* both data placement and migration

Naive combination of prior placement and migration techniques provides *sub-optimal performance* due to *lack of coordination*

Lack extensibility to more devices and configurations


Key Limitations of Prior Techniques

Prior HSS techniques *do not optimize* both data placement and migration

Naive combination of prior placement and migration techniques provides *sub-optimal performance* due to *lack of coordination*


Lack extensibility to more devices and configurations

Lack of Holistic Data Management in HSS




Lack of Holistic Data Management in HSS


*State-of-the-art
data migration technique*




Lack of Holistic Data Management in HSS



Lack of Holistic Data Management in HSS



Lack of Holistic Data Management in HSS



Lack of Holistic Data Management in HSS

The *large latency gap* between Sibyl and Oracle is due to Sibyl's *heuristic migration policy* which does not *adapt to workload and system changes*

The *latency gap becomes wider* in a *cost-optimized HSS* where Sibyl's heuristic migration policy performs *costly data evictions*

Key Limitations of Prior Techniques


Prior HSS techniques *do not optimize* both data placement and migration

Naive combination of prior placement and migration techniques provides *sub-optimal performance* due to *lack of coordination*

Lack extensibility to more devices and configurations

Lack of Coordination in Extended Techniques

- What happens if we combine the state-of-the-art placement and migration techniques?



Lack of Coordination in Extended Techniques

- What happens if we combine the state-of-the-art placement and migration techniques?

Naive combinations provide *sub-optimal performance* because the *constituent policies* are *oblivious* to each other's *decisions*

The extended techniques make *conflicting placement and migration decisions* due to *lack of coordination*

Key Limitations of Prior Techniques

Prior HSS techniques *do not optimize* both data placement and migration



Naive combination of prior placement and migration techniques provide *sub-optimal performance* due to *lack of coordination*

Lack extensibility to more devices and configurations

Lack of Extensibility (1/2)

Prior HSS data-management techniques are rigid, and require significant designer effort to extend the policies to more devices


Changes in HSS configuration




Lack of Extensibility (2/2)

Prior HSS-data management techniques are rigid, and require significant designer effort to extend the policies to more devices

Changes in HSS configuration



Design a new policy



Our Goal

A **holistic data-management mechanism** that

1. ***Performs combined optimization*** of both data placement and data migration policies
2. ***Achieves coordination*** between data placement and data migration policies
3. ***Provides easy extensibility*** to incorporate a wide range of HSS configurations

Harmonia



An *online multi-agent reinforcement learning* technique
for HSS data management

Harmonia consists of *two autonomous, coordinating
RL agents* that co-optimize
data placement and data migration

Talk Outline

Background and Motivation

HSS Data Management using Reinforcement Learning


Harmonia

Evaluation and Key Results

Conclusion


Basics of Reinforcement Learning (RL)

- An algorithmic approach where an RL agent learns to select the best **action** for the current state to maximize long-term **reward**




- Agent stores **Q-values** for *every* state-action pair
 - **Expected return** for taking an action in a state

Formulating HSS Data Management using RL



Harmonia's State





- **7-dimensional** vector of state features

- | | |
|------------------------------|---------------------------------|
| ✓ Request Size | ✓ Free Space in the Fast Device |
| ✓ Request Type | ✓ Current Location of a Page |
| ✓ Access Interval of a Page | ✓ Migration Interval of a Page |
| ✓ Access Frequency of a Page | |

- **State features common for both agents**
 - Captures workload changes and system conditions
- **Limited number of state features**
 - Reduce the implementation overhead
 - RL agent is more sensitive to reward
- We **quantize the state features** into bins to reduce storage overhead

Harmonia's Reward (1/2)

- Defines Harmonia's objective
- Data Placement Agent
 - Performs data placement on the critical path of I/O handling
 - **Objective:** Reduce average I/O request latency of current request





- Harmonia **learns to balance device utilization**
 - Overutilization of high-end device leads to higher latency due to **contention, queuing delays and garbage collection**
 - **Selectively placing less-critical data** on low-end devices preserves high-end device capacity


Harmonia's Reward (2/2)

- Data Migration Agent

- Runs in the background
- **Objective:** Maximizes long-term HSS performance by reorganizing data across HSS devices




Harmonia's Reward (2/2)




- Data Migration Agent

- Runs in the background

- **Objective:** Maximizes long-term HSS performance by reorganizing data across HSS devices



Harmonia's Reward (2/2)



- Data Migration Agent

- Runs in the background

- **Objective:** Maximizes long-term HSS performance by reorganizing data across HSS devices

Performance gains from freed high-end device capacity is seen on future placements


$$\text{Delayed Reward} = (n / \sum L_i) - P_{\text{migr}}$$

Migrate x pages
(e.g., x = 10)


observe next n I/O req. + latencies
(latencies $L_t \dots L_{t+n}$) (e.g., n = 50)

(time)

Harmonia's Reward (2/2)




- Data Migration Agent
 - Runs in the background
 - **Objective:** Maximizes long-term HSS performance by reorganizing data across HSS devices



- Latency encapsulates the device's internal state
 - (e.g., read/write latencies, garbage collection latency, queuing delays, ...)

What is Action?



- Data Placement

- For every new I/O request, the action is to **select a storage device to place** the I/O request data

- Data Migration

- For every page already placed in HSS, **select the storage device to migrate** the data

- Action can be **easily extended** to any number of storage devices

Talk Outline

Background and Motivation


HSS Data Management using Reinforcement Learning

Harmonia


Evaluation and Key Results

Conclusion

Harmonia: Overview



Harmonia: RL Agent Design



More in the Paper

- Coordination between Harmonia's agents
 - Harmonia (with coordination) outperforms its uncoordinated variant by 26.7% (59.8%) on a performance- (cost-) optimized HSS
- Harmonia's adaptability to changes in workload access patterns
- Detailed RL agent design
 - RL algorithm
 - Hyper-parameter tuning
 - Training and inference network design
- Detailed workload characterization
- Detailed analysis of why RL is a good fit for HSS data management
- Detailed background on the prior data placement and migration techniques

More in the Paper

Harmonia: Enhancing Data Placement and Migration in Hybrid Storage Systems via Multi-Agent Reinforcement Learning

Rakesh Nadig[§] Vamanan Arulchelvan[§] Rahul Bera[§] Taha Shahroodi[§] Gagandeep Singh[†]
Andreas Kakolyris[§] İsmail Emir Yüksel[§] Mohammad Sadrosadati[§] Jisung Park[▽]
Onur Mutlu[§]

[§]*ETH Zürich*

[†]*AMD Research*

[▽]*POSTECH*



<https://arxiv.org/pdf/2503.20507>

Talk Outline

Background and Motivation

HSS Data Management using Reinforcement Learning

Harmonia

Evaluation and Key Results


Conclusion

Evaluation Methodology (1/2)


- **Real system** with various HSS configurations
 - Dual-hybrid, tri-hybrid and quad-hybrid storage systems



Cost-Optimized Dual HSS



Performance-Optimized Dual HSS



Evaluation Methodology (2/2)

• Eight Baselines

Data Placement

- **CDE** [Matsui+, Proc. IEEE 2017]
- **Sibyl** [Singh+, ISCA 2022]

Data Migration

- **RNN-HSS** [Doudali+, HPDC 2019]
- **K-SVM** [Shetti+, NAS 2022]

Extended Techniques

- **Sibyl + K-SVM**
- **Sibyl + RNN-HSS**
- **CDE + RL-Migr**
- **SAPM (Single Agent for Placement and Migration)**

• 25 Data-Intensive Workloads

Yahoo Cloud-Serving Benchmark

Cloud Database workloads
(e.g., insert, update, read, scan)

SYSTOR'17

Traffic on enterprise virtual desktop
infrastructure (VDI)

RocksDB

Key-Value Store


MLPerf Storage

Image Classification and Cosmology
Parameter Prediction


Large Language Models

Checkpoint writes, loading of weights and
model parameters, and KV Cache accesses

Performance Analysis (1/2)




Performance-Optimized HSS




Harmonia significantly *reduces average I/O latency* over Sibyl by *co-optimizing and coordinating* the *placement and migration* policies

Performance Analysis (1/2)




Performance-Optimized HSS




Harmonia's average I/O latency is *closer to* Oracle than prior approaches *without the knowledge of workload's future access patterns*

Performance Analysis (2/2)



Cost-Optimized HSS







Harmonia's *proactive background migration* and *coordinated decisions* reduces the *average I/O latency* compared to prior approaches

Extensibility Analysis

Extending Harmonia for **more devices**:

1. **Add a new action** in each agent
2. **Add the remaining capacity** of the new device as a state feature for each agent





Extensibility Analysis

Extending Harmonia for **more devices**:

1. **Add a new action** in each agent
2. **Add the remaining capacity** of the new device as a state feature for each agent

Harmonia provides *greater latency reduction* than prior approaches as the *number of devices increases* in the HSS



Overhead Analysis

- **206 KiB** of total storage cost
 - Experience buffers, inference and training networks
- **32-bit** metadata overhead per page for state features
- Inference Latency - **240ns**
- Training Latency - **53μs (background)**



Small storage overhead



Small inference overhead

More in the Paper (1/3)

- **Throughput (IOPS) evaluation**

- Harmonia provides high end-to-end throughput compared to baseline policies because it's state and reward structures **indirectly captures throughput**

- **Evaluation on unseen workloads**

- Harmonia provides **high performance** benefits when evaluated on unseen workloads that are not used for hyperparameter tuning

- **Performance sensitivity** to

- Migration queue size
- Number of incoming requests considered in migration agent's reward

- **Convergence** of Harmonia's policies

- Both data-placement and data-migration policies converge in less than **8K I/O requests**

More in the Paper (2/3)

- Harmonia's impact on **device lifetimes**
- Evaluation using **multi-programmed workloads**
- Evaluation on **persistent-memory based HSS**
 - Harmonia provides **higher performance** benefits when evaluated on a PMEM-based HSS
- Detailed **overhead analysis**
- More observations and insights from our evaluation

More in the Paper (3/3)

Harmonia: Enhancing Data Placement and Migration in Hybrid Storage Systems via Multi-Agent Reinforcement Learning

Rakesh Nadig[§] Vamanan Arulchelvan[§] Rahul Bera[§] Taha Shahroodi[§] Gagandeep Singh[†]
Andreas Kakolyris[§] İsmail Emir Yüksel[§] Mohammad Sadrosadati[§] Jisung Park[▽]
Onur Mutlu[§]

[§]*ETH Zürich*

[†]*AMD Research*

[▽]*POSTECH*



<https://arxiv.org/pdf/2503.20507>

Harmonia is Open-Source

main 1 Branch 0 Tags

Go to file

Add file

Code

rakeshnadig Add the arXiv link of the paper to the readme 94fcb4c · 20 minutes ago 3 Commits

driver	First Commit	37 minutes ago
harmonia	First Commit	37 minutes ago
LICENSE	First Commit	37 minutes ago
README.md	Add the arXiv link of the paper to the readme	20 minutes ago
requirements.txt	First Commit	37 minutes ago
run_all.py	First Commit	37 minutes ago
setup.py	First Commit	37 minutes ago

README MIT license

Harmonia: Enhancing Data Placement and Migration in Hybrid Storage Systems via Multi-Agent Reinforcement Learning

Harmonia is a multi-agent online reinforcement learning (RL) framework for **holistic data management in hybrid storage systems (HSS)**. Unlike prior work that optimizes either data placement or data migration in isolation, Harmonia jointly optimizes *both* policies in a coordinated manner using two lightweight, autonomous RL agents that adapt online to the current workload and HSS configuration.

About

Harmonia: Enhancing Data Placement and Migration in Hybrid Storage Systems via Multi-Agent Reinforcement Learning

Readme

MIT license

Activity

Custom properties

0 stars

0 watching

0 forks

Releases

No releases published

[Create a new release](#)

Packages

No packages published

[Publish your first package](#)

Contributors 1

 **rakeshnadig** Rakesh Nadig

Languages

<https://github.com/cmu-safari/Harmonia>

Talk Outline

Background and Motivation

HSS Data Management using Reinforcement Learning

Harmonia

Evaluation and Key Results

Conclusion

Conclusion



First work to use *multi-agent reinforcement learning* to optimize data management in hybrid storage systems



Reduces average I/O latency by *29.3%/44.8%* over the *best-performing prior work* on performance-optimized/cost-optimized dual HSS



Provides greater *latency reduction* than the prior approaches *when extended to more storage devices*



Low inference latency and storage *overheads*



Harmonia



Enhancing Data Placement and Migration in Hybrid Storage Systems via Multi-Agent Reinforcement Learning

[Rakesh Nadig](#), Vamanan Arulchelvan, Rahul Bera, Taha Shahroodi,
Gagandeep Singh, Andreas Kosmas Kakolyris, İsmail Emir Yüksel,
Mohammad Sadrosadati, Jisung Park and Onur Mutlu

ICS 2026

SAFARI
ETH zürich

AMD

POSTECH

FAQ (1/2)

- Executive Summary
- Lack of Holistic Data Management in HSS
- Lack of Coordination in Extended Techniques
- Limitations of a Single-Agent RL Technique
- Workload Access Patterns
- State Features in Harmonia
- Training and Inference Network
- Hyperparameter Tuning
- Evaluation Methodology
- Workload Characteristics

FAQ (2/2)

- Multi-Programmed Workloads
- Results
 - Throughput Analysis
 - Device Lifetimes
 - Multi-Programmed Workloads
 - Tail Latency
 - Harmonia's Adaptivity
 - Sensitivity Analysis
 - Write Traffic Distribution
 - Unseen Workloads
 - Impact of Coordination

Executive Summary (1/2)


- **Background:**
 - A **hybrid storage system (HSS)** uses multiple heterogeneous storage devices to provide scalable storage capacity at high performance
 - The performance of an HSS highly depends on the effectiveness of its (1) **data-placement**, and (2) **data-migration** policies
- **Problem:** Two key shortcomings of prior HSS data-management techniques:
 - Prior techniques focus on improving only data-placement or only data-migration policies, but **do not optimize both**
 - Naively combining prior data-placement and data-migration techniques provide **sub-optimal performance** due to **lack of coordination between the two policies**
- **Goal:** Design a holistic data management technique that
 - **optimizes both** data-placement and data-migration policies, and
 - **achieves coordination** between the two policies

Executive Summary (2/2)

- **Contribution:** Harmonia, the first multi-agent online reinforcement learning-based HSS data-management technique that:
 - Performs **combined optimization** of both data placement and data migration policies
 - Achieves **coordination** between data placement and data migration to avoid conflicting decisions
 - Can **easily extend** to any number of storage devices
- **Key Results:** Evaluate on a **real system with multiple HSS configurations** using 25 data-intensive workloads
 - Harmonia **improves latency by 29.3%/44.8%** compared to the state-of-the-art data placement technique in performance-optimized/cost-optimized dual-HSS configuration
 - In a tri-/quad-HSS configuration, Harmonia outperforms the state-of-the-art policy by **39%/40%**
 - Harmonia's performance benefits come with low latency (**240ns** for inference) and storage overheads (**206 KiB** in DRAM for both RL agents together)


Lack of Holistic Data Management in HSS

- Prior techniques
 - **do not optimize** both data placement and migration policies together
 - use **heuristic approaches**, which do not adapt to changes in workload access patterns and HSS conditions





Lack of Holistic Data Management in HSS

- Prior techniques
 - **do not optimize** both data placement and migration policies together
 - use **heuristic approaches**, which do not adapt to changes in workload access patterns and HSS conditions




Lack of Coordination in Extended Techniques

- What happens if we combine the best placement and migration techniques?




Lack of Coordination in Extended Techniques

- *What happens if we combine the best placement and migration techniques?*




Limitations of a Single-Agent RL Technique

- An RL-based technique can adapt to changes in workload and HSS configurations
 - Sibyl is the best-performing prior HSS data-management technique
- Data placement and data migration are two different tasks in HSS with different objectives
- A **single RL agent** based technique **cannot optimize different tasks** concurrently because it relies on **task similarity** to learn multiple tasks



SAPM has **higher latency** than Sibyl because it **cannot learn optimal policies** for two different tasks **concurrently**

Workload Access Patterns



State Features in Harmonia

Feature	Description	# of bins	Encoding (bits)
<i>req_type</i>	Request type (read/write)	2	1
<i>req_size</i>	Request size (in pages)	8	3
<i>acc_intr</i>	Access interval of the requested page	64	8
<i>acc_freq</i>	Access frequency of the requested page	64	8
<i>fast_cap</i>	Free space in the fast storage device	8	3
<i>curr_dev</i>	Storage device where the requested page currently resides	2	1
<i>migr_intr</i>	Migration interval of a page	64	8

Hyper-Parameter Tuning

- Different hyper-parameter configurations were chosen using the design of experiments (DoE) technique

Hyper Parameter	Design Space	Placement Agent	Migration Agent
Discount Factor (γ)	0-1	0.9	0.1
Learning Rate (α)	$1e^{-5} - 1e^0$	$1e^{-3}$	$1e^{-2}$
Exploration Rate (ϵ)	0-1	0.001	0.001
Batch Size	64-256	128	256
Experience Buffer Size	10-10000	1000	1000

Evaluation Methodology

Host System	AMD Ryzen 7 2700G [110] , 8-cores@3.5 GHz, 8×64/32 KiB L1-I/D, 4 MiB L2, 8 MiB L3, 16 GiB RDIMM DDR4 2666 MHz
Storage Devices	Characteristics
H: Intel Optane SSD P4800X [47]	375 GB, PCIe 3.0 NVMe, SLC, R/W: 2.4/2 GB/s, random R/W: 550000/500000 IOPS
M: Intel SSD D3-S4510 [48]	1.92 TB, SATA TLC (3D), R/W: 560/510 MB/s, random R/W: 895000/21000 IOPS
L: Seagate HDD ST1000DM010 [108]	1 TB, SATA 6Gb/s 7200 RPM Max. Sustained Transfer Rate: 210 MB/s
L_{SSD}: ADATA SU630 SSD [111]	960 GB, SATA, TLC, R/W: 520/450 MB/s
PMEM (Emulated): Intel Optane Persistent Memory 200 Series [112]	128 GB, Memory Mode R/W: 7.45/2.25 GB/s (256B)
HSS Configurations	Devices
Performance-Optimized	high-end (H) & middle-end (M)
Cost-Optimized	high-end (H) & low-end (L)
HSS with PMEM	Emulated PMEM (PMEM) & high-end SSD (H)
Tri-HSS	high-end (H) & middle-end (M) & low-end (L)
Quad-HSS	high-end (H) & middle-end (M) & low-end SSD (L _{SSD}) & low-end HDD (L)


Workload Characteristics

Benchmark Suite	Traces	Read %	Avg. Request Size (KB)	Avg. Inter-Request Time (μ s)
SYSTOR17 [262]	LUN0	0.2	31.7	1163.9
	LUN1	0.3	34.2	1864.1
	LUN2	7.6	31.1	1418.9
	LUN3	3.5	42.7	734.5
	LUN4	0.5	26.3	823.1
RocksDB [263]	ssd-00	79.9	108.9	66.4
	ssd-01	73.5	75.1	40.7
	ssd-02	79.9	7.5	3.3
	ssd-03	79.9	9.5	3.5
	ssd-04	79.9	7.8	3.6
YCSB [246]	YCSB-B	51.3	45.9	9.3
	YCSB-C	47.6	54.6	6.5
	YCSB-D	55.9	36.1	8.5
	YCSB-E	52.1	46.6	9.6
	YCSB-F	49.5	53.1	6.6
MLPerf Storage [264]	ResNet50	80.0	172.6	500.1
	CosmoFlow	83.4	180.1	1023.8
LLM [24, 265–267]	LLM-Checkpoint	10.5	256	94.8
	LLM-Weights	25.1	128.0	45.0
	LLM-KVCache	45.0	16.0	24.0
Baleen [247–249] (Unseen Workloads)	Region 1	87.9	3578.9	7.1
	Region 2	78.1	2781.6	6.5
	Region 3	74.4	2084.7	7.6
	Region 4	79.9	2850.8	4.0
	Region 5	66.8	2920.6	3.0

Multi-Programmed Workloads

Mix	Constituent Workloads [246, 262, 263]	Description
mix1	ssd-02 and LUN4	ssd-02 is read-intensive and LUN4 is write-intensive
mix2	LUN1 and ssd-04	LUN1 is write-intensive and ssd-04 is read-intensive
mix3	YCSB-C and YCSB-F	Both have near-equal read-write ratio
mix4	ssd-00, ssd-04, LUN0 and LUN1	Two read-intensive and two write-intensive workloads
mix5	ssd-00, LUN0, YCSB-C and YCSB-F	Read-intensive, write-intensive and two workloads with a near-equal read-write ratio
mix6	YCSB-B, YCSB-D, LUN0, LUN1, LUN4, ssd-00, ssd-02, ssd-03	Two with near-equal read-write ratio, three write-intensive and three read-intensive

Throughput Analysis (1/2)






Throughput Analysis (2/2)



Harmonia improves end-to-end throughput by 49.4% (136.7%) over Sibyl in performance- (cost-) optimized HSS



Impact on Device Lifetimes (1/2)



Impact on Device Lifetimes (2/2)

■ CDE

■ K-SVM

▣ RNN-HSS

▣ Sibyl + K-SVM

▣ Sibyl + RNN-HSS

▣ CDE+RL-Migr

▣ SAPM



■ Sibyl

Harmonia learns to migrate more data in **read-intensive workloads**, since there are infrequent updates from the application

Harmonia migrates less data in **write-intensive workloads** as data is moved during updates from application, which causes **lower write amplification**

Multi-Programmed Workloads (1/2)



Performance-Optimized HSS



Harmonia improves latency by 33% on average over best-performing prior work, Sibyl




Multi-Programmed Workloads (2/2)

Cost-Optimized HSS




Harmonia improves latency by 25% over Sibyl due to faster learning of access pattern variations compared to prior approaches

Tail Latency



Tail Latency



- Fast-Only
- Sibyl
- RNN-HSS
- Oracle
- CDE + RL-Migr
- KSVM
- Harmonia
- CDE
- Sibyl+K-SVM


Prior approaches have **high tail latency** because they **migrate data** in the **critical path of I/O request handling**





Harmonia **improves tail latency** by **migrating data** during **system idle times**



Harmonia's Adaptivity




Sensitivity Analysis



Write Traffic Distribution

Fast Device Writes

Slow Device Writes




(a) Performance-Optimized HSS

(b) Cost-Optimized HSS

Unseen Workloads


- We use Meta's Baleen workloads to test Harmonia's latency on unseen workloads



Harmonia improves performance by 31.2% (31.5%) over Sibyl due to adaptive data placement and data migration

Impact of Coordination

■ Sibyl ■ Harmonia (No Coordination) ■ Harmonia (With Coordination)



Harmonia outperforms its uncoordinated variant by 26.7% (59.8%)
by avoiding conflicting decisions